

## 2x2 Single-mode Mechanical Optic Switch

### Features

- Low insertion loss
- Wide wavelength range
- Low crosstalk
- High stability and reliability
- Epoxy-free optical path



### Applications

1. R&D in laboratory
2. System monitoring
3. Configurable OADM
4. Metropolitan area networks
5. Component testing

### Pins Definitions

Optical Route		Port1 To Port3/Port2 To Port4		Port1 To Port4/Port2 To Port3	
Electricity driving	Latching	Pin10	Pin6	Pin1	Pin5
		V+	GND	V+	GND
	State	Pin2-3, Pin8-9 open		Pin2-3, Pin8-9 close	
	Latching	Pin3-4, Pin7-8 close		Pin3-4, Pin7-8 open	

### Specifications

Parameter	Value			
Operating wavelength (nm)	1310± 40 or 1550±40		1310/1550 ± 40	
Insertion Loss (dB)	P Grade	A Grade	P Grade	A Grade
	< 0.8	< 1.0	< 1.0	< 1.2
WDL (dB)	≤ 0.25	≤ 0.25	≤ 0.25	≤ 0.30

Contact your OSTenp representative for information on specifications and availability.

PDL (dB)	≤ 0.15	≤ 0.15	≤ 0.15	≤ 0.15
TDL (dB)	< 0.20	< 0.25	< 0.20	< 0.25
Crosstalk (dB)	>55	>55	>55	>55
Repeatability (dB)	< ± 0.02			
Return Loss(dB)	> 55			
Switching Time (ms)	<10 (Typ.4)			
Coil resistance (Pins 1-5 or 6-10) (ohms)	178 ± 10%			
Operating voltage (V)	5			
Rated power (mW)	500			
Durability	>10 million			
Operating Temperature(°C)	0 ~ +70			
Storage Temperature (°C)	-45 ~ +85			
Fiber Type	SMF-28			
Fiber Length (m)	1.0 +/- 0.1			
Dimensions (LxWxH) (mm)	L29 × W15 × H10			

### Ordering Information

Optical switch	Port Type	Control Type	Wavelength	Fiber Type	Pigtail Type	Fiber Length	Connector
	2X2=2X2	L=Latching N=Non-latching	85=850nm 98=980nm 13=1310nm 15=1550nm 35=1310&1550 nm 00=customized	SM=SMF-28E M5=MM50/125 M6=MM62.5/125 S= customized	09=900um loose tube 90=900um tight buffer 20=2.0mm fiber 30=3.0mm fiber	0.5=0.5m 10=1.0m 15=1.5m 20=2.0m  S= customized	NA=None FP=FC/PC FA=FC/APC SP=SC/PC SA=SC/APC LP=LC/UPC LA=LC/APC MU=MU/UPC S= customized

\* 詳細は、お手数ですがお問い合わせフォームにお願いします。

Contact your OSTenp representative for information on specifications and availability.