

POFスイッチ  
POF Switch



5-Port 100Base-FX POF Switch 仕様例

項目	内容
Network Ports	5x100Mbps POF Ports
Standards Compliance	IEEE 802.3u Fast Ethernet
Environmental Specifications	Operating Temperature: 0C to 50C.
	Storage Temperature: -40C to 85C.
	Operating Humidity: 5%-90% RH non condensing
Dimensions (W x D x H) & Weight	140mm x 80mm x 30mm
	0.5 kg
Power Specifications	AC 90-260V,50/60Hz 5V/2.5A internal AC Adapter

12-Port 100Base-FX POF Switch with 2-Port Giga SFP 仕様例

項目	内容
Network Ports	12 POF Ports 100Base-FX 2-Port Gigabit TP+SFP ports
Standards Compliance	IEEE 802.3 IEEE 802.3u IEEE 802.3ab,IEEE 802.3z IEEE 802.3x IEEE 802.3q,IEEE 802.3p
Environmental Specifications	Operating Temperature: 0C to 50C.
	Storage Temperature: -40C to 85C.
	Operating Humidity: 5%-90% RH non condensing
Dimensions (W x D x H) & Weight	450mm x 150mm x 50mm
	4.5 kg
Power Specifications	AC 90-260V,50/60Hz 5V/4A internal AC Adapter Power Consumption: 50W

\* 特殊仕様のPOFスイッチの製作も可能です。詳細は、お手数ですがお問い合わせフォームをお願いします。

Contact your OSTenp representative for information on specifications and availability.